

# Comfort / Titan Series

## Fluid Warmers



Safety is a priority with Enthermics Series fluid warmers. Ensure fluids are safely warmed to recommended temperatures through the WarmSafe™ zone heating system. WarmRight® technology provides the right temperature for the right product to meet healthcare guidelines for IV and irrigation fluids.

The patient-friendly Comfort Series allows you to put aesthetically pleasing warming units right where they are needed, allowing nurses and aides to maximize their time.

The durable Titan Series, using 201&430 stainless steel, provides years of worry-free service

The lighting inside the warmers softens the patient's room, placing more emphasis on comfort and care.

**WarmSafe Zone Heating:** Heat is evenly balanced throughout the chamber to provide safe fluid warming.

**Convenient:** Keep in patient or procedure rooms with this counter top model.

**Service:** Our worldwide support team is dedicated to providing quality equipment. We walk with you every step of the way to maximize your return on investment.

**Glass Door:** Energy-efficient coated glass door reflects heat back into the cavity.

**Mobile:** Optional casters

**Made in the USA** with a commitment to quality

**Warranty:** 3-year parts/1-year labor (US/Canada only)

An ISO 13485:2016 certified company

### Standard Features

- Windowed door
- Organizational basket
- Epoxy-coated interior surfaces
- Programmable control with temperature lock feature
- Interior lighting with a comforting blue glow
- Temperature management access point
- Four (4) non-skid rubber feet



**2.5 ft<sup>3</sup>**

DC250L / EC250L

**3.5 ft<sup>3</sup>**

EC350L (Titan Series only)



Adjustable temperature range of

32°-40°C (90°-104°F) adjustable injection mode

32°-66°C (90°-150°F) adjustable irrigation mode

Accurate temperature

IRR +0/-1.67°C (-3°F)

INJ +0/-1.10°C (-2°F)

### Comfort Series



DC250L

### Titan Series



EC250L



EC350L

### Configurations (select one of each)

#### Series

Comfort (DC)  Titan (EC)

#### Size

2.5 ft<sup>3</sup>  3.5 ft<sup>3</sup> (Titan Series only)

#### Door Assembly

Windowed door (standard)  Solid door (Titan Series only)

#### Door Swing

Right hinged (standard)  Left hinged

#### Door lock

No lock (standard)  Manual lock (Titan Series only)

#### Baskets - Comfort Series

2 baskets (standard)  1 basket

#### Baskets - Titan Series

1 basket (standard-EC250L)  
 2 baskets (EC250L)  
 1 basket and 1 shelf (standard-EC350L)

#### Electrical

120V 1PH  220V 1PH  230V 1PH

### Accessories (select all that apply)

**Bumper and Caster Assembly** 3" (76mm) casters, 2 rigid; 2 swivel with Brake; overall height increases by 5" (127mm)

DC250L (5017546)  EC250L or EC350L (5017548)

**Caster Package with Plate** 3" (76mm) casters, 2 rigid; 2 with Brake; overall height increases by 5" (127mm)

DC250L (5017542)  EC250L or EC350L (5017544)

#### Mobile


3.5" (89mm) casters, 2 swivel; 2 swivel with brake (500206);

#### Anchorage (4 required)


Anti-tip bracket (1014403)

# Comfort/Titan Series Fluid Warmers

## EC/DC250L



## EC350L



# Comfort/Titan Series Fluid Warmers



## Specification



Top: 1"  
Left: 1"  
Right: 1"  
Back: 3"



Model	Exterior (H x W x D)	Interior (H x W x D)	Net Weight
DC250L	22"(559mm) x 18.5"(470mm) x 22.0"(559mm)	15.25"(387mm) x 15.5"(394mm) x 18.75"(476mm)	67 lbs (30 kg)
EC250L	22"(559mm) x 18.5"(470mm) x 23.5"(597mm)	15.25"(387mm) x 15.5"(394mm) x 18.75"(476mm)	67 lbs (30 kg)
EC350L	28"(711mm) x 18.5"(470mm) x 23.5"(597mm)	21.25"(540mm) x 15.5"(394mm) x 18.75"(476 mm)	91 lbs (41 kg)

### Ship Dimensions (L x W x H)\*

EC/DC250L	35" x 23" x 30"	116 lbs
EC350L	35" x 23" x 42"	144 lbs

### Ship Weight\*

\*Domestic ground shipping information. Contact factory for export weight and dimensions.



ELECTRIC

	V	Ph	Hz	A	kW	Plug Configuration
EC/DC250L	120	1	60	3.7	0.44	NEMA 5-15P; 15A 125V Plug; Hospital Grade
	220	1	50/60	2.0	0.44	CEE 7/7 220-230V Plug
	230	1	50/60	1.9	0.44	BS 1363 Plug; CEE 7/7 220-230V Plug
EC350L	120	1	60	3.7	0.44	NEMA 5-15P; 15A 125V Plug; Hospital Grade
	220	1	50/60	2.0	0.44	CEE 7/7 220-230V Plug
	230	1	50/60	1.9	0.44	BS 1363 Plug; CEE 7/7 220-230V Plug



IPX-0

\*Other international plugs are available, contact the manufacturer for more information.

\*\*Electrical connections must meet all applicable federal, state and local codes.

## CONTACT US

4000 S.E. Columbia Way | Vancouver, Washington 98661 | U.S.A.  
Phone: 800-822-3501 | [enthermics.com](http://enthermics.com)